

Outdoor Use

LED 墙壁照明

LED SURFACE  
BULKHEAD



# OVAL LED Bulkhead IP65

CLASS I

Material:  
Aluminum/PC



AC85-265V

Diffuser: Opal PC Diffuser



Oval Bulkhead

SMD LEDs  
**LED**

Outlook: silver grey/black/white


Note:  
open cable included




FCD-A001S  
FCD-A001L



FCD-A002S  
FCD-A002L







FCD-A003S  
FCD-A003L



FCD-A004S  
FCD-A004L

Die casting aluminum lamp body;  
Opal white PC/frosted glass diffuser;  
Silicone rubber gasket;  
Powder coating finish;



	FCD-A001S	FCD-A001L
A	218	280
B	133	185
C	62	91

	FCD-A001S	FCD-A001L
A	218	280
B	133	185
C	62	91

	FCD-A001S	FCD-A001L
A	218	280
B	133	185
C	62	91

	FCD-A001S	FCD-A001L
A	218	280
B	133	185
C	62	91

Model No.	Input Voltage	Beam Angle	Watts	LED Type	LED QTY	Color Temperature	Flux (lm)	Work Temp.	IP Class	Safety Class	Lifetime
FCD-A001/2/3/4S	AC85-265V	120deg	10W	SMD5730	20pcs	2700-7000K	70lm/w	-20~+40°	IP65	I	≥30000
FCD-A001/2/3/4S	AC85-265V	120deg	20W	SMD5730	40pcs	2700-7000K	70lm/w	-20~+40°	IP65	I	≥30000



# Round LED Bulkhead IP65

CLASS I

Material:  
Aluminum/PC



AC85-265V

Diffuser: Opal PC Diffuser



Round Bulkhead



SMD LEDs

Outlook: silver grey/black/white

Note:  
open cable included



FCD-A005X




FCD-A005C



FCD-A005V







FCD-A005B



FCD-A005N

Die casting aluminum lamp body;  
Opal white PC/frosted glass diffuser;  
Silicone rubber gasket;  
Powder coating finish;



Model No.	Input Voltage	Beam Angle	Watts	LED Type	LED QTY	Color Temperature	Flux (lm)	Work Temp.	IP Class	Safety Class	Lifetime
FCD-A005	AC85-265V	120deg	20W	SMD5730	60pcs	2700-7000K	70lm/w	-20~+40°	IP65	I	≥30000
FCD-A005	AC85-265V	120deg	30W	SMD5730	60pcs	2700-7000K	70lm/w	-20~+40°	IP65	I	≥30000



# Rectangular LED Bulkhead Ip65

Material:  
Aluminum/PC



AC85-265V

Diffuser: Opal PC Diffuser




Rectangular Bulkhead




SMD LEDs

Outlook: silver grey/black/white

Note:  
open cable included




FCD-B001A




FCD-B001B

Die casting aluminum lamp body;  
Opal white PC/frosted glass diffuser;  
Silicone rubber gasket;  
Powder coating finish;



FCD-B001C



FCD-B001D









Model No.	Input Voltage	Beam Angle	Watts	LED Type	LED QTY	Color Temperature	Flux (lm)	Work Temp.	IP Class	Safety Class	Lifetime
FCD-B001A/B	AC85-265V	120deg	20W	SMD5730	60pcs	2700-7000K	70lm/w	-20~+40°	IP65	I	≥30000
FCD-B001C/D	AC85-265V	120deg	20W	SMD5730	60pcs	2700-7000K	70lm/w	-20~+40°	IP65	I	≥30000




# Round LED Bulkhead Ip65


CLASS I

Material: Aluminum/PC  AC85-265V Diffuser: Opal PC Diffuser     **Round Bulkhead**

 SMD LEDs Outlook: silver grey/black/white **Note: open cable included**








FCD-B002A





FCD-B002B

Model No.	Input Voltage	Beam Angle	Watts	LED Type	LED QTY	Color Temperature	Flux (lm)	Work Temp.	IP Class	Safety Class	Lifetime
FCD-B002A/B	AC85-265V	120deg	20W	SMD5730	60pcs	2700-7000K	70lm/w	-20~+40°	IP65	I	≥30000
FCD-B002A/B	AC85-265V	120deg	30W	SMD5730	60pcs	2700-7000K	70lm/w	-20~+40°	IP65	I	≥30000


# Square LED Bulkhead Ip65

Material: Aluminum/PC  AC85-265V Diffuser: Opal PC Diffuser     **Square Bulkhead**

 SMD LEDs Outlook: silver grey/black/white **Note: open cable included**



FCD-B003A



FCD-B003B

Model No.	Input Voltage	Beam Angle	Watts	LED Type	LED QTY	Color Temperature	Flux (lm)	Work Temp.	IP Class	Safety Class	Lifetime
FCD-B003A/B	AC85-265V	120deg	20W	SMD5730	60pcs	2700-7000K	70lm/w	-20~+40°	IP65	I	≥30000
FCD-B003A/B	AC85-265V	120deg	30W	SMD5730	60pcs	2700-7000K	70lm/w	-20~+40°	IP65	I	≥30000



## Features:

