



**COMMERCIAL
LED Lighting**

2019

2018

2016

2014

2012



DESIGNLIGHTS
 CONCEPT

ISO9001:2015

CE

RoHS

Brand Lighting Co., Ltd is an ISO 9001:2015 certified professional LED lighting manufacturer, specializing in researching, developing and manufacturing full range of led lighting solutions. With clear marketing orientation, sustained technical innovation and internationally-updated management philosophy, customer oriented conceptions, Brand continues to grow and establish itself to be a more professional manufacturer.

At present, Brand has more than 400 staffs which specialized in producing and developing led indoor lighting products, and covers an area of 50000 square meters. Since the company established, we have committed ourselves to make people's lives more comfortable and high-efficient. We and our compaies are working hard at making technology progress to let people enjoy the changes of new technology.

Company Culture

Action No excuse Confidence Responsibility Efficiency Orientation Honesty

A. Honesty Culture: Honesty is the foundation of all, being the first rule of every action!

B. Customer Culture: Nothing is important, but you!

C. Innovation Culture: Lighting the world through innovation!

D. Service Culture: Always here for you!

E. Responsibility Culture: Keep the world green, reduce power plant emissions, go LED today!


Certification



Workshop



Production equipment



Testing instrument



LED PANEL LIGHT SERIES





LED PANEL LIGHT SERIES



CE RoHS

CE RoHS



MODEL:THD-A003



-  120deg
-  CRI ≥80Ra
-  Embedded
-  IP IP40
-  -25~+45 deg

-  No dimming
85-265V AC
-  Dimmable
90-120V /220-240V






Power	3W	6W	12W	18W
Luminous flux	270lm	540lm	1080lm	1620lm
Size(mm) RD	φ 85	φ 120	φ 170	φ 225
Size(mm) SQ	85*85	120*120	170*170	225*255





CRI options:2700K,3000K,4000K,5000K,6000K
 Surface Color:Orange+White
 LED brand:SMD2835 Epistar,Sanan,Samsung
 Life Span:30000hrs
 Light body material:aluminum+lgp
 Dimmable: Triac,0/1~10V.DALI dimming



MODEL:THD-A004



-  120deg
-  CRI ≥80Ra
-  Embedded
-  IP IP40
-  -25~+45 deg

-  No dimming
85-265V AC
-  Dimmable
90-120V /220-240V

Power	3W	6W	12W	18W
Luminous flux	270lm	540lm	1080lm	1620lm
Size(mm) RD	φ 85	φ 120	φ 170	φ 225
Size(mm) SQ	85*85	120*120	170*170	225*255



CRI options:2700K,3000K,4000K,5000K,6000K
 Surface Color:Orange+White
 LED brand:SMD2835 Epistar,Sanan,Samsung
 Life Span:30000hrs
 Light body material:aluminum+lgp
 Dimmable: Triac,0/1~10V.DALI dimming

LED PANEL LIGHT SERIES






LED PANEL LIGHT SERIES


CE RoHS


CE RoHS

MODEL:THD-A005








-  120deg
-  CRI ≥80Ra
-  Embedded
-  IP IP40
-  -25~+45 deg


 No dimming
85-265V AC


 Dimmable
90-120V /220-240V

MODEL:THD-A006





-  120deg
-  CRI ≥80Ra
-  Embedded
-  IP IP40
-  -25~+45 deg

 No dimming
85-265V AC

 Dimmable
90-120V /220-240V

Power	3W	6W	12W	18W
Luminous flux	270lm	540lm	1080lm	1620lm
Size(mm) RD	φ 85	φ 120	φ 170	φ 225
Size(mm) SQ	85*85	120*120	170*170	225*255

Power	3W	6W	12W	18W
Luminous flux	270lm	540lm	1080lm	1620lm
Size(mm) RD	φ 85	φ 120	φ 170	φ 225
Size(mm) SQ	85*85	120*120	170*170	225*255



CRI options:2700K,3000K,4000K,5000K,6000K



Surface Color:Orange+White

LED brand:SMD2835 Epistar,Sanan,Samsung

Life Span:30000hrs

Light body material:aluminum+lgp

Dimmable: Triac,0/1~10V.DALI dimming



CRI options:2700K,3000K,4000K,5000K,6000K

Surface Color:Orange+White

LED brand:SMD2835 Epistar,Sanan,Samsung

Life Span:30000hrs

Light body material:aluminum+lgp

Dimmable: Triac,0/1~10V.DALI dimming

LED PANEL LIGHT SERIES

LED PANEL LIGHT SERIES

CE RoHS

CE RoHS

MODEL:THD-A007



- 120deg CRI ≥80Ra
- Embedded IP IP40
- 25~+45 deg

- No dimming
85-265V AC
- Dimmable
90-120V /220-240V




- 120deg CRI ≥80Ra
- Embedded IP IP40
- 25~+45 deg


- No dimming
85-265V AC
- Dimmable
90-120V /220-240V

Power	5W	9W	15W	22W
Luminous flux	500lm	900lm	1500lm	2200lm
Size(mm) RD	φ 85	φ 120	φ 170	φ 225
Size(mm) SQ	85*85	120*120	170*170	225*255

Power	5W	9W	15W	22W
Luminous flux	500lm	900lm	1500lm	2200lm
Size(mm) RD	φ 85	φ 120	φ 170	φ 225
Size(mm) SQ	85*85	120*120	170*170	225*255



CRI options:2700K,3000K,4000K,5000K,6000K
 Surface Color:Orange+White
 LED brand:SMD2835 Epistar,Sanan,Samsung
 Life Span:30000hrs
 Light body material:aluminum+lgp
 Dimmable: Triac,0/1~10V.DALI dimming



CRI options:2700K,3000K,4000K,5000K,6000K
 Surface Color:Orange+White
 LED brand:SMD2835 Epistar,Sanan,Samsung
 Life Span:30000hrs
 Light body material:aluminum+lgp
 Dimmable: Triac,0/1~10V.DALI dimming

LED PANEL LIGHT SERIES




LED PANEL LIGHT SERIES

CE RoHS

CE RoHS

MODEL:THD-A001



-  120deg
-  CRI ≥80Ra
-  Embedded
-  IP IP40
-  -25~+45 deg


 No dimming
85-265V AC

 Dimmable
90-120V /220-240V

MODEL:THD-A002





-  120deg
-  CRI ≥80Ra
-  Surface Mounted
-  IP IP40
-  -25~+45 deg

 No dimming
85-265V AC

 Dimmable
90-120V /220-240V

Power	3W	4W	6W	9W	12W	15W	18W	24W
Luminous flux	240lm	320lm	480lm	720lm	960lm	1200lm	1440lm	1920lm
Size(mm) RD	φ 85	φ 105	φ 120	φ 145	φ 170	φ 200	φ 225	φ 300
Size(mm) SQ	85*85	105*105	120*120	145*145	170*170	200*200	225*255	300*300

Power	6W	12W	18W	24W
Luminous flux	480lm	960lm	1440lm	1920lm
Size(mm) RD	φ 120	φ 170	φ 225	φ 300
Size(mm) SQ	120*120	170*170	225*255	300*300



CRI options:2700K,3000K,4000K,5000K,6000K



Surface Color:White

LED brand:SMD2835 Epistar,Sanan,Samsung

Life Span:30000hrs

Light body material:aluminum+lgp

Dimmable: Triac,0/1~10V.DALI dimming



CRI options:2700K,3000K,4000K,5000K,6000K

Surface Color:White

LED brand:SMD2835 Epistar,Sanan,Samsung

Life Span:30000hrs

Light body material:aluminum+lgp

Dimmable: Triac,0/1~10V.DALI dimming

LED PANEL LIGHT SERIES






LED PANEL LIGHT SERIES


CE RoHS


CE RoHS

MODEL:THD-B001



-  120deg
-  CRI ≥80Ra
-  Embedded
-  IP40
-  -25~+45 deg

 No dimming
85-265V AC

 Dimmable
90-120V /220-240V

Power	10W	20W
Luminous flux	880lm	1760lm
Size(mm)	295*295*H10	295*295*H10

CRI options:2700K,3000K,4000K,5000K,6000K


Surface Color:Silver/White

LED brand:Epistar,Sanan,Samsung

Life Span:30000hrs





Light body material:aluminum+lgp


Dimmable: Triac,0/1~10V.DALI dimming.




MODEL:THD-B002



-  120deg
-  CRI ≥80Ra
-  Embedded
-  IP40
-  -25~+45 deg

 No dimming
85-265V AC

 Dimmable
90-120V /220-240V

Power	18W	24W
Luminous flux	1580lm	2110lm
Size(mm)	595*295*H10	595*295*H10

CRI options:2700K,3000K,4000K,5000K,6000K


Surface Color:Silver/White

LED brand:Epistar,Sanan,Samsung

Life Span:30000hrs

Light body material:aluminum+lgp

Dimmable: Triac,0/1~10V.DALI dimming.



LED PANEL LIGHT SERIES





LED PANEL LIGHT SERIES

CE RoHS

CE RoHS

MODEL:THD-B003




-  120deg  CRI ≥80Ra
-  Embedded  IP40
-  -25~+45 deg

 No dimming
85-265V AC

 Dimmable
90-120V /220-240V

Power	36W	48W	56W	72W
Luminous flux	3160lm	4220lm	4920lm	6330lm
Size(mm)	595*595*H10	595*595*H10	595*595*H10	595*595*H10



CRI options:2700K,3000K,4000K,5000K,6000K

Surface Color:Silver/White

LED brand:Epistar, Sanan, Samsung






Life Span:30000hrs


Light body material:aluminum+Igp

Dimmable: Triac,0/1~10V,DALI dimming

MODEL:THD-B004




-  120deg  CRI ≥80Ra
-  Embedded  IP40
-  -25~+45 deg

 No dimming
85-265V AC

 Dimmable
90-120V /220-240V

Power	36W	48W	56W	72W
Luminous flux	3160lm	4220lm	4920lm	6330lm
Size(mm)	595*595*H10	595*595*H10	595*595*H10	595*595*H10



CRI options:2700K,3000K,4000K,5000K,6000K

Surface Color:Silver/White

LED brand:Epistar, Sanan, Samsung

Life Span:30000hrs

Light body material:aluminum+Igp

Dimmable: Triac,0/1~10V,DALI dimming

LED DOWNLIGHT SERIES






LED DOWNLIGHT SERIES



CE RoHS

CE RoHS






MODEL:THD-C007





-  15/24/38deg  ≥80Ra
-  Embedded  IP40
-  -25~+45 deg

-  No dimming
85-265V AC
-  Dimmable
90-120V /220-240V




-  15/24/38deg  ≥80Ra
-  Embedded  IP40
-  -25~+45 deg


-  No dimming
85-265V AC
-  Dimmable
90-120V /220-240V

Power	6W	15W	20W	25W	35W
Luminous flux	600lm	1500lm	2000lm	2500lm	3500lm
Size(mm)	D90*H52	D115*H65	D140*H76	D200*H108	D230*H120
Cut-Out(mm)	φ 65	φ 90	φ 115	φ 160	φ 195

Power	8W	20W	30W
Luminous flux	800lm	2000lm	3000lm
Size(mm)	D95*H98	D120*H120	D145*H150
Cut-Out(mm)	φ 75	φ 95	φ 130



CRI options:2700K,3000K,4000K,5000K,6000K
 Other light color:Blue,Green,Red.
 LED brand:Philips,CREE,Citizen
 Life Span:50000hrs
 Light body material:aluminum+glass
 Dimmable: Triac,0/1~10V,DALI dimming



CRI options:2700K,3000K,4000K,5000K,6000K
 Other light color:Blue,Green,Red.
 LED brand:Philips,CREE,Citizen
 Life Span:30000hrs
 Light body material:aluminum+glass
 Dimmable: Triac,0/1~10V,DALI dimming

LED DOWNLIGHT SERIES






LED DOWNLIGHT SERIES



CE RoHS

CE RoHS

MODEL:THD-C009





-  15/24/38deg  ≥80Ra
-  Embedded  IP40
-  -25~+45 deg

-  No dimming
85-265V AC
-  Dimmable
90-120V /220-240V




-  
-  Embedded  IP40
-  -25~+45 deg


-  No dimming
85-265V AC
-  Dimmable
90-120V /220-240V

Power	8W	12W	15W
Luminous flux	800lm	1200lm	1500lm
Size(mm)	D83*H61	D85*H63	D85*H63
Cut-Out(mm)	φ 75	φ 70	φ 70

Power	8W	12W	15W
Luminous flux	800lm	1200lm	1500lm
Size(mm)	D85*85*H61	D85*85*H63	D85*85*H63
Cut-Out(mm)	φ 75*75	φ 70*70	φ 70*70



CRI options:2700K,3000K,4000K,5000K,6000K
 Other light color:Blue, Green,Red.
 LED brand:Philips, CREE, Citizen
 Life Span:50000hrs
 Light body material:aluminum+glass
 Dimmable: Triac,0/1~10V,DALI dimming



CRI options:2700K,3000K,4000K,5000K,6000K
 Other light color:Blue, Green,Red.
 LED brand:Philips, CREE, Citizen
 Life Span:30000hrs
 Light body material:aluminum+glass
 Dimmable: Triac,0/1~10V,DALI dimming

LED DOWNLIGHT SERIES






LED DOWNLIGHT SERIES


CE RoHS

CE RoHS

MODEL:THD-C011








-  38deg
-  CRI ≥80Ra
-  Embedded
-  IP IP40
-  -25~+45 deg


 No dimming
85-265V AC

 Dimmable
90-120V /220-240V

MODEL:THD-C012




-  120deg
-  CRI ≥80Ra
-  Embedded
-  IP IP40
-  -25~+45 deg

 No dimming
85-265V AC


 Dimmable
90-120V /220-240V

Power	5W	7W	10W	15W	20W	30W	40W
Luminous flux	500lm	700lm	100lm	1500lm	2000lm	3000lm	4000lm
Size(mm)	D100	D106	D115	D143	D180	D190	D230
Cut-Out(mm)	φ 70	φ 80	φ 90	φ 110	φ 145	φ 160	φ 190

Power	5W	7W	10W	15W	20W	30W	40W
Luminous flux	400lm	560lm	800lm	1200lm	1600lm	2400lm	3200lm
Size(mm)	D100	D106	D115	D143	D180	D190	D230
Cut-Out(mm)	φ 70	φ 80	φ 90	φ 110	φ 145	φ 160	φ 190



CRI options:2700K,3000K,4000K,5000K,6000K
Other light color:Blue, Green,Red.
LED brand:Philips, Citizen, CREE, Bridgelux, Epistar
Life Span:50000hrs
Light body material:aluminum+glass
Dimmable: Triac,0/1~10V,DALI dimming



CRI options:2700K,3000K,4000K,5000K,6000K
Other light color:Blue, Green,Red.
LED brand:SMD Epistar, Sanan.
Life Span:30000hrs
Light body material:aluminum+pmma
Dimmable: Triac,0/1~10V,DALI dimming






LED DOWNLIGHT SERIES


LED DOWNLIGHT SERIES

CE RoHS

CE RoHS

MODEL:THD-C013






-  60deg
-  CRI ≥80Ra
-  Embedded
-  IP IP40
-  -25~+45 deg


 No dimming
85-265V AC

 Dimmable
90-120V /220-240V



MODEL:THD-C014

-  50deg
-  CRI ≥80Ra
-  Embedded
-  IP IP40
-  -25~+45 deg


 No dimming
85-265V AC

 Dimmable
90-120V /220-240V




Power	5W	7W	12W	18W	20W	30W
Luminous flux	500lm	700lm	1200lm	1800lm	2000lm	3000lm
Size(mm)	D100*H50	D118*H60	D145*H75	D170*H85	D190*H95	D230*H105
Cut-Out(mm)	φ 80	φ 100	φ 125	φ 150	φ 160	φ 200

Power	5W	7W	12W	18W	20W	30W
Luminous flux	400lm	560lm	960lm	1440lm	1600lm	2400lm
Size(mm)	D100*H50	D118*H60	D145*H75	D170*H85	D190*H95	D230*H105
Cut-Out(mm)	φ 80	φ 100	φ 125	φ 150	φ 160	φ 200



CRI options:2700K,3000K,4000K,5000K,6000K
Other light color:Blue, Green,Red.
LED brand:Philips, Citizen, CREE, Bridgelux, Epistar
Life Span:50000hrs
Light body material:aluminum+glass
Dimmable:Triac,0/1~10V.DALI dimming



CRI options:2700K,3000K,4000K,5000K,6000K
Other light color:Blue, Green,Red.
LED brand:SMD Epistar, Sanan.
Life Span:30000hrs
Light body material:aluminum+pmma
Dimmable:Triac,0/1~10V.DALI dimming

LED DOWNLIGHT SERIES




LED DOWNLIGHT SERIES

CE RoHS

CE RoHS

MODEL:THD-C001








-  60deg
-  CRI ≥80Ra
-  Embedded
-  IP IP40
-  -25~+45 deg


 No dimming
85-265V AC


 Dimmable
90-120V /220-240V

MODEL:THD-C002




-  50deg
-  CRI ≥80Ra
-  Embedded
-  IP IP40
-  -25~+45 deg

 No dimming
85-265V AC


 Dimmable
90-120V /220-240V

Power	10W	15W	20W	30W	40W
Luminous flux	1000lm	1500lm	2000lm	3000lm	4000lm
Size(mm)	D108*H52	D142*H65	D158*H75	D185*H88	D226*H108
Cut-Out(mm)	φ 95	φ 125	φ 140	φ 170	φ 210

Power	7W	12W	20W	30W	40W
Luminous flux	700lm	1200lm	2000lm	3000lm	4000lm
Size(mm)	D90*H80	D120*H80	D147*H100	D200*H103	D230*H103
Cut-Out(mm)	φ 75	φ 100	φ 120	φ 165	φ 200



CRI options:2700K,3000K,4000K,5000K,6000K
Other light color:Blue, Green,Red.
LED brand:Philips, Citizen, CREE, Brigdelux, Epistar
Life Span:30000hrs
Light body material:aluminum+glass
Dimmable: Triac, 0/1~10V.DALI dimming



CRI options:2700K,3000K,4000K,5000K,6000K
Other light color:Blue, Green,Red.
LED brand:Philips, Citizen, CREE, Brigdelux, Epistar
Life Span:30000hrs
Light body material:aluminum+glass
Dimmable: Triac, 0/1~10V.DALI dimming

LED DOWNLIGHT SERIES

LED DOWNLIGHT SERIES

CE RoHS

CE RoHS

MODEL:THD-C003








-  60deg
-  CRI ≥80Ra
-  Embedded
-  IP IP40
-  -25~+45 deg


 No dimming
85-265V AC


 Dimmable
90-120V /220-240V

MODEL:THD-C004




-  50deg
-  CRI ≥80Ra
-  Embedded
-  IP IP40
-  -25~+45 deg

 No dimming
85-265V AC


 Dimmable
90-120V /220-240V

Power	10W	20W	30W	40W
Luminous flux	800lm	1600lm	2400lm	3200lm
Size(mm)	D100*H50	D165*H70	D190*H80	D225*H90
Cut-Out(mm)	φ 85	φ 150	φ 175	φ 210

Power	7W	12W	18W	24W	30W
Luminous flux	560lm	960lm	1440lm	1920lm	2400lm
Size(mm)	D90*H30	D120*H30	D140*H30	D170*H30	D220*H30
Cut-Out(mm)	φ 75	φ 105	φ 125	φ 155	φ 205



CRI options:2700K,3000K,4000K,5000K,6000K
Other light color:Blue, Green,Red.
LED brand:Philips, Citizen, CREE, Bridgelux, Epistar
Life Span:50000hrs
Light body material:aluminum+glass
Dimmable: Triac,0/1~10V,DALI dimming



CRI options:2700K,3000K,4000K,5000K,6000K
Other light color:Blue, Green,Red.
LED brand:SMD Epistar, Sanan.
Life Span:30000hrs
Light body material:aluminum+pmma
Dimmable: Triac,0/1~10V,DALI dimming

LED DOWNLIGHT SERIES






LED DOWNLIGHT SERIES


CE RoHS

CE RoHS

MODEL:THD-C005








-  24/38deg  CRI ≥80Ra
-  Embedded  IP IP40
-  -25~+45 deg


 No dimming
85-265V AC

 Dimmable
90-120V /220-240V

MODEL:THD-C006




-  30/45deg  CRI ≥80Ra
-  Embedded  IP IP40
-  -25~+45 deg

 No dimming
85-265V AC


 Dimmable
90-120V /220-240V

Power	5/7W	10/12W	15W	20W	30W
Luminous flux	450/630lm	900/1080lm	1350lm	1800lm	2700lm
Size(mm)	D90*H63	D110*H74	D140*H95	D140*H110	D160*H140
Cut-Out(mm)	φ 70	φ 95	φ 115	φ 115	φ 145

Power	3W	5/7W	9/12W	15/18W
Luminous flux	270lm	450/630lm	810/1080lm	1350/1620lm
Size(mm)	D86*H46	D110*H55	D140*H55	D160*H73
Cut-Out(mm)	φ 75	φ 95	φ 120	φ 140



CRI options:2700K,3000K,4000K,5000K,6000K
Other light color:Blue, Green, Red.
LED brand:Philips, Citizen, CREE, Bridgelux, Epistar
Life Span:30000hrs
Light body material:aluminum+glass
Dimmable:Triac, 0/1~10V.DALI dimming



CRI options:2700K,3000K,4000K,5000K,6000K
Other light color:Blue, Green, Red.
LED brand:Philips, Citizen, CREE, Bridgelux, Epistar
Life Span:30000hrs
Light body material:aluminum+glass
Dimmable: Triac, 0/1~10V.DALI dimming

LED DOWNLIGHT SERIES






LED DOWNLIGHT SERIES

CE RoHS

CE RoHS



MODEL:THD-C015






-  10/23/36deg  ≥80Ra
-  Embedded  IP40
-  -25~+45 deg


 No dimming
85-265V AC


 Dimmable
90-120V /220-240V



MODEL:THD-C016

-  50deg  ≥80Ra
-  Embedded  IP40
-  -25~+45 deg

 No dimming
85-265V AC

 Dimmable
90-120V /220-240V


Power	15W	20/30W	35W	40W	55W
Luminous flux	1500lm	2000/3000lm	3500lm	4000lm	5500lm
Size(mm)	D110	D140	D165	D195	D195
Cut-Out(mm)	φ 90	φ 120	φ 145	φ 175	φ 175

Power	35W	45W
Luminous flux	3500lm	4500lm
Size(mm)	D130	D165
Cut-Out(mm)	φ 120	φ 145



CRI options:2700K,3000K,4000K,5000K,6000K
Other light color:Blue,Green,Red.
LED brand:Philips,CREE,Citizen COB
Life Span:30000hrs
Light body material:aluminum+glass
Dimmable:Triac,0/1~10V.DALI dimming

CRI options:2700K,3000K,4000K,5000K,6000K
Other light color:Blue,Green,Red.
LED brand:Philips,CREE,Citizen COB
Life Span:30000hrs
Light body material:aluminum+glass
Dimmable:Triac,0/1~10V.DALI dimming



LED DOWNLIGHT SERIES






LED DOWNLIGHT SERIES

CE RoHS

CE RoHS



MODEL: MZTD-A001SQ






-  38deg  CRI ≥80Ra
-  Embedded  IP40
-  -25~+45 deg


 No dimming
85-265V AC

 Dimmable
90-120V /220-240V



MODEL: MZTD-A004QD

-  45/60deg  CRI ≥80Ra
-  Embedded  IP40
-  -25~+45 deg

 No dimming
85-265V AC

 Dimmable
90-120V /220-240V

Power	10W	15W	20W	30W
Luminous flux	1000lm	1500lm	2000lm	3000lm
Size(mm)	80*80*H103	100*100*H120	120*120*H130	150*150*H142

Power	15W	20W	25W	30W
Luminous flux	1500lm	2000lm	2500lm	3000lm
Size(mm)	D117*H115	D137*H115	D169*H139	D200*H139

CRI options:2700K,3000K,4000K,5000K,6000K


Other light color:Blue, Green,Red.

LED brand:Philips,Citizen,CREE,Brigdelux,Epistar

Life Span:30000hrs

Light body material:aluminum+glass

Dimmable: Triac,0/1~10V.DALI dimming



CRI options:2700K,3000K,4000K,5000K,6000K

Other light color:Blue, Green,Red.

LED brand:Philips,Citizen,CREE,Brigdelux,Epistar

Life Span:30000hrs

Light body material:aluminum+glass

Dimmable: Triac,0/1~10V.DALI dimming







CE RoHS

CE RoHS

MODEL:GDD-A001





-  15/24deg  CRI ≥80Ra
-  Track light  IP IP40
-  -25~+45 deg


 No dimming
85-265V AC


 Dimmable
90-120V /220-240V

MODEL:GDD-A002



-  15/24deg  CRI ≥80Ra
-  Track Light  IP Ip40
-  -25~+45 deg

 No dimming
85-265V AC

 Dimmable
90-120V /220-240V

Power:20W/30W

Luminous Flux:95-100lm/w

Product Dimension:143*93*H178

CRI options:2700K,3000K,4000K,5000K,6000K


Other light color:Blue,Green,Red.

LED brand:Philips,CREE,Citizen.

Life Span:30000hrs

Light body material:Aluminum

Dimmable: Triac,0/1~10V,DALI dimming



Power:18W/20W/24W

Luminous Flux:95-100lm/w

Product Dimension:135*94*H147

CRI options:2700K,3000K,4000K,5000K,6000K


Other light color:Blue,Green,Red.

LED brand:Philips,CREE,Citizen.

Life Span:30000hrs

Light body material:Aluminum

Dimmable: Triac,0/1~10V,DALI dimming



LED TRACK LIGHT SERIES





LED TRACK LIGHT SERIES

CE RoHS

CE RoHS



MODEL:GDD-A003




-  15/24deg  CRI ≥80Ra
-  Track light  IP IP40
-  -25~+45 deg


 No dimming
85-265V AC


 Dimmable
90-120V /220-240V



MODEL:GDD-A004

-  15/24deg  CRI ≥80Ra
-  Track Light  IP Ip40
-  -25~+45 deg

 No dimming
85-265V AC

 Dimmable
90-120V /220-240V

Power:20W/35W

Luminous Flux:100-110lm/w

Product Dimension:D105*L155*H260mm

CRI options:2700K,3000K,4000K,5000K,6000K

Other light color:Blue,Green,Red.

LED brand:Philips,CREE,Citizen.

Life Span:30000hrs

Light body material:Aluminum

Dimmable: Triac,0/1~10V.DALI dimming



Power:20W/35W

Luminous Flux:100-110lm/w

Product Dimension:D90*L136*H260mm

CRI options:2700K,3000K,4000K,5000K,6000K

Other light color:Blue,Green,Red.

LED brand:Philips,CREE,Citizen.

Life Span:30000hrs

Light body material:Aluminum

Dimmable: Triac,0/1~10V.DALI dimming



LED TRACK LIGHT SERIES





LED TRACK LIGHT SERIES

CE RoHS

CE RoHS



MODEL:GDD-A005

-  15/24deg  $\geq 80Ra$
-  Track light  IP40
-  -25~+45 deg


 No dimming
85-265V AC

 Dimmable
90-120V /220-240V



MODEL:GDD-A006

-  15/24deg  $\geq 80Ra$
-  Track Light  Ip40
-  -25~+45 deg

 No dimming
85-265V AC

 Dimmable
90-120V /220-240V

Power:20W/35W

Luminous Flux:100-110lm/w

Product Dimension:D80*L130

CRI options:2700K,3000K,4000K,5000K,6000K

Other light color:Blue,Green,Red.

LED brand:Philips,CREE,Citizen

Life Span:30000hrs

Light body material:Aluminum

Dimmable: Triac,0/1~10V,DALI dimming



Power:8W/10W/12W

Luminous Flux:100-110lm/w

Product Dimension:D65*L83*H100mm

CRI options:2700K,3000K,4000K,5000K,6000K

Other light color:Blue,Green,Red.

LED brand:Philips,CREE,Citizen

Life Span:30000hrs

Light body material:Aluminum

Dimmable: Triac,0/1~10V,DALI dimming








LED TUBE LIGHT SERIES


LED TUBE LIGHT SERIES


CE RoHS

CE RoHS

MODEL:T8

-  270deg  ≥80Ra
-  With Bracket  IP20
-  -25~+45 deg


 No dimming
85-265V AC


 Dimmable
90-120V /220-240V



MODEL:T8-Integrative

-  180deg  ≥80Ra
-  Surface Mounted  Ip20
-  -25~+45 deg


 No dimming
85-265V AC

 Dimmable
90-120V /220-240V




Power	9W	12W	18W	24W
Luminous flux	900lm	1200lm	1800lm	2400lm
Dimension	2ft	3ft	4ft	5ft

Power	9W	12W	18W	24W
Luminous flux	900lm	1200lm	1800lm	2400lm
Size(mm)	2ft	3ft	4ft	5ft



CRI options:2700K,3000K,4000K,5000K,6000K
 Other light color:Blue,Green,Red.
 LED brand:SMD Epistar,Samsung,Sanan
 Life Span:30000hrs
 Light body material:aluminum+PC cover
 Dimmable: Triac dimming



CRI options:2700K,3000K,4000K,5000K,6000K
 Other light color:Blue,Green,Red.
 LED brand:SMD Epistar,Samsung,Sanan
 Life Span:30000hrs
 Light body material:aluminum+PC cover
 Dimmable: Triac dimming



LED TUBE LIGHT SERIES


LED TUBE LIGHT SERIES

CE RoHS

CE RoHS

MODEL:T8-Glass Tube

-  360deg  ≥80Ra
-  With Bracket  IP20
-  -25~+45 deg






 No dimming
85-265V AC


 Dimmable
90-120V /220-240V

CRI options:2700K,3000K,4000K,5000K,6000K
Other light color:Blue,Green,Red.
LED brand:SMD Epistar,Samsung,Sanan
Life Span:30000hrs
Light body material:Glass Tube
Dimmable: Triac dimming




MODEL:T5

-  180deg  ≥80Ra
-  Surface Mounted  Ip20
-  -25~+45 deg

 No dimming
85-265V AC

 Dimmable
90-120V /220-240V

CRI options:2700K,3000K,4000K,5000K,6000K
Other light color:Blue,Green,Red.
LED brand:SMD Epistar,Samsung,Sanan
Life Span:30000hrs
Light body material:aluminum+PC cover
Dimmable: Triac dimming



Power	9W	12W	18W	24W
Luminous flux	900lm	1200lm	1800lm	2400lm
Dimension	2ft	3ft	4ft	5ft

Power	5W	9W	12W	18W	24W
Luminous flux	500lm	900lm	1200lm	1800lm	2400lm
Size(mm)	1ft	2ft	3ft	4ft	5ft

A series of horizontal dashed lines spanning the width of the page, intended for writing notes.



.....

Brand Lighting Co., Limited

Tel: +86-13686972518 / +86-13169807260

Email: info@brand-light.com

Website: www.brand-light.com /
brandlight.en.alibaba.com

Add: No.2103, No.2 Fazhandadao, Pengjiang District,
Jiangmen City, Guangdong, China, 529000.